



TYPICAL INTERIOR GLASS FLOOR
COMMERCIAL/RESIDENTIAL INSTALLATION
NOT TO SCALE

NOTE:

INNOVATIVE BUILDING PRODUCTS, INC. ASSUMES NO RESPONSIBILITY FOR THE DESIGN, CONSTRUCTION OR FABRICATION OF THE SUPPORTING AND/OR CONTAINMENT OPENING. DESIGN OF SUCH IS THE SOLE RESPONSIBILITY OF THE PROJECT ENGINEER / ARCHITECT. INNOVATIVE BUILDING PRODUCTS, INC. IS ONLY RESPONSIBLE FOR THE ENGINEERING AND STRUCTURAL INTEGRITY OF THE FLOOR GRID SYSTEM ITSELF.

THE SUPPORTING STRUCTURE MUST BE DESIGNED TO SUPPORT:

1. SELF WEIGHT = 11.75 PSF
2. LIVE LOAD = 125 PSF
3. ANY ADDITIONAL LOADS REQUIRED BY THE GOVERNING BUILDING CODES.

MAXIMUM CLEAR SPAN WITHOUT SUPPORT BEAMS (L/500):

- SPANNING MEMBER DIRECTION - 75" FOR 8" GLASS*
- SPANNING MEMBER DIRECTION - 48" FOR 48" GLASS*
- SPACER MEMBER DIRECTION - INFINITY

MAXIMUM CONTINUOUS LENGTH WITH SUPPORT BEAMS AS REQUIRED:

- SPANNING MEMBER DIRECTION - INFINITY
- SPACER MEMBER DIRECTION - INFINITY

Because IBP has no control over installation, workmanship, accessory materials or conditions of application, no representation or warranty, expressed or implied, either as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE is made as to the performance or results of an installation of this product.

Innovative Building Products, Inc.
P.O. Box 425 Fort Worth, TX 76101
Phone: (800) 932-2263
Fax: (817) 332-1406
Plant: 206 Dotson St. Denton, TX 76205

GlassWalk™
IBP GLASS FLOOR SYSTEMS

FAST TRACK
STONE system™

IBP
glass floor grid system™

GF-1

JAN. 2017